

- 89%
- 0.95
-
- IP66
-
- Class 2 SELV



EUV-042SxxxPS

90 ~ 305 Vac

12 Vdc	90 ~ 305 Vac	0~3500 mA	42 W	84%	0.96	0.95	EUV-042S012PS ⁽³⁾
24 Vdc	90 ~ 305 Vac	0~1750 mA	42 W	86%	0.96	0.95	EUV-042S024PS ⁽³⁾
36 Vdc	90 ~ 305 Vac	0~1160 mA	42 W	87%	0.96	0.95	EUV-042S036PS ⁽³⁾
48 Vdc	90 ~ 305 Vac	0~875 mA	42 W	89%	0.96	0.95	EUV-042S048PS ⁽⁴⁾

- 1 UL, FCC : 100-277Vac; UL & FCC : 100~ 240Vac
 2 220Vac, 100%
 3 Class 2 &
 4 Class 2 , Class 2

	90 Vac	-	305 Vac	
	47 Hz	-	63 Hz	
	-	-	0.75 mA	277Vac/60Hz
	-	-	0.70 mA	IEC60598-1; 240Vac/ 60Hz
	-	-	0.6 A	100Vac, 100%
	-	-	0.3 A	220Vac, 100%
	-	-	70 A	220Vac 25 10% -
I ² t	-	-	0.16 A ² s	10% = 100 μs

	0.90	-	-	100~ 277Vac,50-60Hz,75% ~ 100% (31.5~ 42W)
	-	-	20%	

	-5%Vo		5%Vo	
Vo = 12 V Vo = 24 V Vo = 36 V Vo = 48 V	- - - -	- - - -	3 V 4 V 4 V 4 V	20MHz 0.1µF 10µF
Vo = 12 V Vo = 24 V Vo = 36 V Vo = 48 V	- - - -	- - - -	16 V 28 V 40 V 52 V	
	-	-	10%Vo	100%
	-	-	±2%	100%

	327,000 hours	-	-	120Vac 25 ,80% (MIL-HDBK-217F)
	-	116,000 Hours	-	120Vac 80% 60
	-40	-	+90	
	-40		+70	: 10% RH to 100% RH
	-40		+85	: 5% RH to 100% RH
(L × W × H) (L × W × H)	3.74 × 2.76 × 1.26 95 × 70 × 32			
	-	390 g	-	


25°C

UL/CUL	UL8750, UL 1310, CAN/CSA-C22.2 No. 250.13, CAN/CSA-C22.2 No. 223-M91
CE	EN 61347-1, EN61347-2-13
KS	KS C 7655
EN 55015 ⁽¹⁾	Conducted Emission Test & Radiated Emission Test
EN 61000-3-2	Harmonic current emissions
EN 61000-3-3	Voltage fluctuations & flicker
FCC Part 15 ⁽¹⁾	ANSI C63.4 Class B This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: [1] this device may not cause harmful interference, and [2] this device must accept any interference received, including interference that may cause undesired operation.
EMS	
EN 61000-4-2	Electrostatic Discharge (ESD): 8 kV air discharge, 4 kV contact discharge
EN 61000-4-3	Radio-Frequency Electromagnetic Field Susceptibility Test-RS


EMS	
EN 61000-4-4	Electrical Fast Transient / Burst-EFT
EN 61000-4-5	Surge Immunity Test: AC Power Line: Differential Mode 2 kV
EN 61000-4-6	Conducted Radio Frequency Disturbances Test-CS
EN 61000-4-8	Power Frequency Magnetic Field Test
EN 61000-4-11	Voltage Dips
EN 61547	Electromagnetic Immunity Requirements Applies To Lighting Equipment

1 EMI


() EMI




EUV-042S012PS
效率 vs. 输出电流




EUV-042S024PS
效率 vs. 输出电流




EUV-042S036PS
效率 vs. 输出电流




EUV-042S048PS
效率 vs. 输出电流





	1.1 lo	1.4 lo	1.7 lo	
-Tc	110		75	



RoHS 2011/65/EU

EU 2015/863

